

# EcoSmart

kvm-tec



# Full HD



EcoSmart



- for DVI-D in dongle format
- USB 2.0 transparent
- Sound embedded
- Full HD videos in real time
- Point to point or switching via OSD and Switching Manager
- Mouse glide & Switch
- powered by USB
- Zero space factor for much space in the server room with zero RU
- Upgrade: VGA

ECOSmart in CAT version for distances up to 150m/492ft and resolutions up to 1920 x 1200 @60 Hz.

ECOSmart is compatible with standard network components. In the KVM-4Future Matrix Switching System up to 2000 endpoints or for point to point connections.

Power can be supplied via USB or an external power supply.

In-house developed USB technology allows great flexibility in connecting to USB HID devices, such as mice and keyboards, tablets, etc.

ECOSmart is like all kvm-tec extenders too fast for slow latencies - latency 0,47 ms. With the perfect in-house developed video compression a lossless video and audio transmission is possible.

KVM-TEC Gewerbepark Mitterfeld 1 A 2523 Tattendorf Austria www.kvm-tec.com	IHSE GmbH Benzstr.1 88094 Oberteuringen Germany www.ihse.com	IHSE USA LLC 1 Corp.Dr.Suite Cranburry NJ 08512 USA www.ihseusa.com	IHSE GMBH Asia 158Kallang Way,#07-13A 349245 Singapore www.ihse.com	IHSE China Co.,Ltd Room 814 Building 3, Kezhu Road Guangzhou PRC www.ihse.com.cn
---	--	---	---	--

Zero space