

Digital microphone array with 4xMEMS | Supports AEC/AGC/ANS
3 level microphone cascading with HALO-VX10-V2.

HALO-COM-MIC

WyreStorm

Specification Sheet



WyreStorm – Powerful. Reliable. Simple.

Introduction:

Add-on microphone for use with the HALO-VX10-V2 video bar. Connect this mic to expand the pickup range. Connects to the VX10 via an included USB cable. The HALO-COM-MIC can be cascaded up to 3 times. Microphone Includes AEC, background noise reduction, automatic gain control to make all participants feel like they are in the same room. Pick up range is 3 – 5 meters.

Specification:

Audio and Video	
Inputs	1x 10 Pin- USB MINI Female
Outputs	1x 10 Pin- USB MINI Female
Microphone	4 x MEMS Omnidirectional digital microphone array
Communication and Control	
Mute	1x Mute Button
USB	USB MINI
Power	
Power Supply	Powered by HALO-VX10 v2
Environmental	
Operating Temperature	0 to + 45°C (32 to + 113 °F), 10% to 90%, non-condensing
Storage Temperature	-20 to +70°C (-4 to + 158 °F), 10% to 90%, non-condensing
Dimension and Weight	
Height * Width * Depth	21.5mm*100mm*100mm
Regulatory	
Safety and Emission	CE FCC RoHS RCM EAC UKCA